



7087BQ

FlowTech LTE® 1D Standard Non-belted Full Body Harness, Triple-Lock Quick Connect Leg Buckles

FEATURES

- Lightweight Flowscape® shoulder yoke and sub-pelvic leg pads deliver evaporative breathability
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit
- Features lightweight forged aluminum alloy dorsal D-ring
- Also features exclusive locking quick-connect leg buckles for added protection against accidental disengagement
- Quick-connect chest buckle features visual indicator showing positive connection
- Complies with ANSI Z359.11-2014

MATERIAL SPECIFICATIONS

Webbing: Polyester; 5,000 lb min. static strength

D-ring: Aluminum alloy; 5,000 lb min. static strength

Buckles and Adjusters: Aluminum alloy and plated alloy steel; 3,372 lb min. static strength

PERFORMANCE SPECIFICATIONS

Static Strength: 3,600 lb min.

ANSI User Capacity: 130 to 310 lb max.

OSHA User Capacity: 130 to 425 lb max.

SIZES & PART NUMBERS

- 7087BQS - Small
- 7087BQM - Medium
- 7087BQL - Large
- 7087BQXL - XL
- 7087BQ2X - 2X

COMPLIANT WITH:

ANSI Z359.11-2014

OSHA 1926.502 and 1910.66

