



7093B

FlowTech LTE® 3D Standard Non-belted Full Body Harness, Tongue Buckle Leg Adjustment

FEATURES

- Lightweight Flowscape® shoulder yoke and sub-pelvic leg pads deliver evaporative breathability
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit
- Features lightweight forged aluminum alloy dorsal and hip D-rings
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Quick-connect chest buckle features visual indicator showing positive connection
- Complies with ANSI Z359.11-2014

MATERIAL SPECIFICATIONS

Webbing: Polyester; 5,000 lb min. static strength

D-rings: Aluminum alloy; 5,000 lb min. static strength

Buckles and Adjusters: Aluminum alloy and plated alloy steel; 3,372 lb min. static strength

PERFORMANCE SPECIFICATIONS

Static Strength: 3,600 lb min.

ANSI User Capacity: 130 to 310 lb max.

OSHA User Capacity: 130 to 425 lb max.

SIZES & PART NUMBERS

- 7093BS - Small
- 7093BM - Medium
- 7093BL - Large
- 7093BXL - XL
- 7093B2X - 2X
- 7093B3X - 3X

COMPLIANT WITH:

ANSI Z359.11-2014

OSHA 1926.502 and 1910.66

