



# 7226CLE

DuraTech® Leading Edge SRL with 15' Galvanized Steel Cable and Aluminum Housing

## FEATURES

---

- 7/32" galvanized steel cable lifeline with load-indicating swivel snap hook
- Internal inertial braking system with dual disc brakes provides superior deceleration.
- Integrated external ViewPack® energy absorber enhances braking system and preserves lifeline integrity
- Side-payout housing design and lifeline recoil spring deliver smooth operation and help reduce nuisance lock-up
- Integrated lifeline hand-grip simplifies dorsal connection
- Stackable aluminum housing design and handle provide easy installation and storage
- Includes extra large anchorage carabiner with 2-1/4" gate opening
- Complies with ANSI Z359.14-2014

## MATERIAL SPECIFICATIONS

---

**Cable:** 7/32" galvanized steel; 3,400 lb min. static strength

**Energy Absorber:** Polyester tear-away

**Lifeline Connector:** Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

**Anchorage Connector:** Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

## PERFORMANCE SPECIFICATIONS

---

**Static Strength:** 3,000 lb min.

**ANSI SRL Class:** Class A

**Avg. Arrest Force:** 1,350 lb

**Max. Arrest Force:** 1,800 lb

**Max. Arrest Distance:** 24"

**ANSI User Capacity:** 130 to 310 lb max.

**OSHA User Capacity:** 130 to 310 lb max.



OSHA 1926.502 and 1910.66