

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

C0917070a

Declaration Date

9.20.17

Tested Item #

82562

6' SAL Single Leg Viewpack w/Tie-Back D-Rings

Additional Items Conforming Under this Declaration:

825623A

82562B

8256210

825623A

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

ANSI Z359.13-2013

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

X

Level 3

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2005

Level 2: FallTech Lab
Within the Scope of
ISO/IEC Standard 17025:2005

Level 3: Independent 3rd Party Lab
accredited to
ISO/IEC Standard 17025:2005

Supporting
Documentation

PC-1262

Authorized Signature

Name

Mark Sasaki

Title

Director of Engineering

Date

5.15.19



International Accreditation Service, Inc
3060 Saturn St, Ste 100
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594
ISO/IEC 17025:2005
Alexander Andrew Inc dba FallTech

Exova
3883 East Eagle Drive
Anaheim
California
USA
92807

T: +1 (714) 630-3003
F: +1 (714) 630-4443
E: sales@exova.com
W: www.exova.com



Testing. Advising. Assuring.

September 25, 2017

FallTech Testing Laboratory
1306 S. Alameda Street
Compton, CA 90221

Attention: Jay Sponholz
Quality Manager

Subject: **Attestation of Witnessing Testing**
Exova OCM Job # 371394-8
FallTech P.O.: OPEN
Report No.: PC-1262
Base Part No. 82562
Description: Energy Absorbing Lanyard

Dear Mr. Sponholz:

The purpose of this attestation is to attest to the fact that a representative of Exova OCM was on site at FallTech's facilities to confirm suitability of the equipment used, calibration status of the equipment and to witness testing performed by FallTech employees. Details of this visit are included below:



- Date of Testing:
 - September 19, 2017
- Exova OCM Test Witness:
 - 9/19/17 - Nolan Schatzle
- FallTech Test Operators:
 - Yesbet Sierra/Jay Sponholz
- Specification:


ANSI Z359. 13-2013 Sections: 4.5, 4.11, 4.12, 4.13.1, 4.13.2, 4.13.3

- Equipment Calibration Interval
 - 1 year, except weights which are 5 years

Attached to this attestation is the test report generated by FallTech Testing Laboratory. Exova OCM test witness certifies the report accurately presents the testing performed on the samples identified.

Test Report #	Date	Base Part #	Description	Sample ID's	Results
PC-1262	9/19/17	82562	Energy Absorbing Lanyard	4018104	Pass
				4018094	
				4018096	
				4018104	
				4018094	
				4018096	
				4018102	
				4018100	
				4018093	
				4018101	
				4018106	
				4018099	
				4018097	
				4018103	
				4018091	
4018108					
4018105					
4018107					

Test Witness Signature: Nolan Schatzle Technician Mechanical Laboratory	<i>(Signed for and on behalf of Exova-OCM)</i> 	
---	--	---

Approval Signature: Victor Mendez Production Manager	<i>(Signed for and on behalf of Exova-OCM)</i> 
---	--

This attestation shall not be reproduced except in full, without the written approval of Exova-OCM. The laboratory has witnessed the testing the material / items supplied by the client as sampled by the client. The testing is not within Exova OCM's L.A.B scope of testing and was not performed at Exova OCM.



FallTech Test Report

Test Report No.	PC-1262	Rpt. Date	9/20/2017	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.13-2013 4.5, 4.11, 4.12, 4.13.1, 4.13.2, 4.13.3				
Part No.	82562	Part No. Revision	A				
Part Description	Energy Absorbing Lanyard						
Test Request No.	PC-1262	Date Complete	9/19/2017				
Test Operator(s)	Yesbet Sierra / Jay Sponholz						

Material/Sample Identification

Sample ID	Description
4018104	Energy Absorbing Lanyard
4018094	Energy Absorbing Lanyard
4018096	Energy Absorbing Lanyard
4018104	Energy Absorbing Lanyard
4018094	Energy Absorbing Lanyard
4018096	Energy Absorbing Lanyard
4018102	Energy Absorbing Lanyard
4018100	Energy Absorbing Lanyard
4018093	Energy Absorbing Lanyard
4018101	Energy Absorbing Lanyard
4018106	Energy Absorbing Lanyard
4018099	Energy Absorbing Lanyard
4018097	Energy Absorbing Lanyard
4018103	Energy Absorbing Lanyard
4018091	Energy Absorbing Lanyard
4018108	Energy Absorbing Lanyard
4018105	Energy Absorbing Lanyard
4018107	Energy Absorbing Lanyard



FallTech Test Report

Test Report No.	PC-1262	Rpt. Date	9/20/2017	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.13-2013 4.5, 4.11, 4.12, 4.13.1, 4.13.2, 4.13.3				
Part No.	82562	Part No. Revision	A				
Part Description	Energy Absorbing Lanyard						
Test Request No.	PC-1262	Date Complete	9/19/2017				

Test Summary

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.13-2013 4.5	Arrest Distance	≤ 48"	39.7"	Pass
	Max Arrest Force	≤ 1800 Lbf	996.5 Lbf	Pass
	Avg Arrest Force	≤ 900 Lbf	767.6 Lbf	Pass
ANSI Z359.13-2013 4.5	Arrest Distance	≤ 48"	40.0"	Pass
	Max Arrest Force	≤ 1800 Lbf	989.8 Lbf	Pass
	Avg Arrest Force	≤ 900 Lbf	775.5 Lbf	Pass
ANSI Z359.13-2013 4.5	Arrest Distance	≤ 48"	40.5"	Pass
	Max Arrest Force	≤ 1800 Lbf	1017.0 Lbf	Pass
	Avg Arrest Force	≤ 900 Lbf	751.4 Lbf	Pass
ANSI Z359.13-2013 4.11	Static Strength	≥ 5000 Lbf	5054.7 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013 4.11	Static Strength	≥ 5000 Lbf	5054.0 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013 4.11	Static Strength	≥ 5000 Lbf	5055.5 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013 4.12	Static Strength	≥ 3600 Lbf	3647.7 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013 4.12	Static Strength	≥ 3600 Lbf	3659.3 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013 4.12	Static Strength	≥ 3600 Lbf	3640.9 Lbf	Pass
	Hold	≥ 1 Minute	1 Minute	Pass
ANSI Z359.13-2013 4.13.1	Arrest Distance	≤ 48"	40.6"	Pass
	Max Arrest Force	≤ 1800 Lbf	1063.5 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	758.4 Lbf	Pass
ANSI Z359.13-2013 4.13.1	Arrest Distance	≤ 48"	41.6"	Pass
	Max Arrest Force	≤ 1800 Lbf	1022.1 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	748.7 Lbf	Pass
ANSI Z359.13-2013 4.13.1	Arrest Distance	≤ 48"	42.0"	Pass
	Max Arrest Force	≤ 1800 Lbf	971.6 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	773.4 Lbf	Pass



FallTech Test Report

Test Report No.	PC-1262	Rpt. Date	9/20/2017	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.13-2013 4.5, 4.11, 4.12, 4.13.1, 4.13.2, 4.13.3				
Part No.	82562	Part No. Revision	A				
Part Description	Energy Absorbing Lanyard						
Test Request No.	PC-1262	Date Complete	9/19/2017				


Test Summary (Continued)

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.13-2013 4.13.2	Arrest Distance	≤ 48"	21.5"	Pass
	Max Arrest Force	≤ 1800 Lbf	1186.9 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	865.1 Lbf	Pass
ANSI Z359.13-2013 4.13.2	Arrest Distance	≤ 48"	31.0"	Pass
	Max Arrest Force	≤ 1800 Lbf	1089.4 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	851.6 Lbf	Pass
ANSI Z359.13-2013 4.13.2	Arrest Distance	≤ 48"	29.5"	Pass
	Max Arrest Force	≤ 1800 Lbf	1205.6 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	858.6 Lbf	Pass
ANSI Z359.13-2013 4.13.3	Arrest Distance	≤ 48"	44.0"	Pass
	Max Arrest Force	≤ 1800 Lbf	1017.2 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	736.9 Lbf	Pass
ANSI Z359.13-2013 4.13.3	Arrest Distance	≤ 48"	42.5"	Pass
	Max Arrest Force	≤ 1800 Lbf	1003.8 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	726.0 Lbf	Pass
ANSI Z359.13-2013 4.13.3	Arrest Distance	≤ 48"	45.6"	Pass
	Max Arrest Force	≤ 1800 Lbf	997.3 Lbf	Pass
	Avg Arrest Force	≤ 1125 Lbf	730.6 Lbf	Pass

Conclusion

Based upon the samples provided to the Lab:
 FallTech P/N 82562 Rev. A meets the requirements of ANSI Z359.13-2013

Report Signatories and Approval

Lab Quality Manager		Date	9/20/2017
Witnessed by	Nolan Schatzle 	Date	9-28-17

